

data sheet



Superdope Anaerobic Thread Sealant LEED information

Superdope is a state-of-the-art high strength, anaerobic pipe joint sealant that cures anaerobically, therefore, has no solvents leaking out of the sealant, leaving behind leak paths. Provides 100% sealing capability and does not shrink when curing to allow failure at a later date.

Superdope is manufactured and packaged in the United States.

This letter will detail the potential contribution of Superdope Anaerobic Thread Sealant to the LEED Green Building System in accordance with LEED-requirements for New Construction & Major Renovations.

In reference to LEED® Material and Resources – Recycled Content, Superdope can be classified as post-consumer recycled content. All materials can be recycled.

The raw materials all come from natural resources. All packaging can also be recycled.

In reference to LEED® Material and Resources – A minimum of 50% of the raw materials used in manufacturing the Superdope is sourced and processed within a 500-miles radius of our manufacturing facility in Alpharetta, GA.

Superdope has a volatile organic content (VOC) of 5.4% based on weight (mg/liter) 59.4 grams per liter.

The information contained herein is produced in good faith and is believed to be reliable but is for guidance only. ARGCO and its agents cannot assume liability or responsibility for results obtained in the use of its product by persons whose methods are outside or beyond our control. It is the user's responsibility to determine the suitability of any of the products, methods of use, or preparation prior to use, mentioned in our literature. It is the user's responsibility to observe and adapt such precautions as may be advisable for the protection of personnel and property in the handling and use of any of our products.

**FOR MORE INFORMATION CALL ARGCO AT 1-800-854-1015
OR LOG ONTO WWW.ARGCO.COM**