



“E” dimension includes exposed rod threads beyond bottom of the hex nut. Exposed rod thread dimension is equal to the diameter of the rod used.



Materials/Finishes	Plain Carbon Steel (11FB)	Electro-Galvanized (11FG)
	Hot-Dip Galvanized (11FHDG)	T-304 Stainless (11FSS)
	T-316 Stainless (11FSX)	
Variants:	N/A	
Service:	Designed for the suspension of non-insulated stationary pipe where space is limited.	
Approvals:	Complies with MSS SP-58 and SP-69 (Type #1).	
Ordering:	Specify figure number, finish and pipe size.	
Notes:	Upper locknut must be tightened securely to assure proper hanger performance.	

PIPE SIZE	PIPE OD	BOLT	A	B	C	E	F	WGT EACH (LBS)	MAX REC LOAD (LBS)
1-1/2	1.900	1/4	3/8	2-1/8	3-1/8	1-5/16	5/16	0.42	250
2	2.375	1/4	3/8	2-1/2	3-11/16	1-5/8	7/16	0.46	300
2-1/2	2.875	5/16	1/2	2-7/8	4-3/16	1-7/8	7/16	0.78	500
3	3.500	5/16	1/2	3-5/8	5-3/8	2-9/16	11/16	0.98	500
3-1/2	4.000	5/16	1/2	4-1/16	6-1/16	2-15/16	3/4	1.36	500
4	4.500	3/8	5/8	4-1/16	6-5/16	3-1/8	3/16	1.38	700
5	5.563	1/2	5/8	4-7/8	7-5/8	3-1/2	5/8	2.08	700
6	6.625	1/2	3/4	5-1/2	8-7/8	3-7/8	7/16	2.82	900
8	8.625	5/8	3/4	6-3/8	10-7/8	4-5/8	5/16	4.34	1000
10	10.75	3/4	7/8	8-5/8	14	6-7/8	1-1/2	8.06	1800
12	12.50	3/4	7/8	9-5/8	16	7-5/8	2-9/16	18.05	1800

PROJECT INFORMATION			APPROVAL STAMP
Project:			Notes:
Address:			
Contractor:			
Engineer:			
Date:			
Approved	Approved as Noted	Not Approved	