

King Combination Nipples



Applications

- Recommended for low-pressure discharge and suction service for compatible liquids, sizes 1-1/4" and above are not for compressible products such as air or nitrogen
- King combination nipples are not recommended for steam
- The working pressure may vary with the construction of the hose, the type of clamping system used, and the application, consult Dixon® for recommendations
- In accordance with the Association for Rubber Products Manufacturers (ARPM) bulletin for oil suction and discharge hose, a coupled length of hose in any size, should be tested to 1-1/2 times the working pressure and held for fifteen minutes without leaking or coupling movement, for additional information and detailed instruction on testing procedures, see the Association for Rubber Products Manufacturers (ARPM) handbook

NPT Threaded End with Knurled Wrench Grip

G



| Size | Opt Qty | Unplated Steel Part # | Plated Steel Part # | Brass Part # | Aluminum Part # |
|--------|---------|-----------------------|---------------------|--------------|-----------------|
| 1/2" | 50 | ST1 | STC1 | BST1 | AST1 |
| 3/4" | 50 | ST5 | STC5 | BST5 | AST5 |
| 1" | 50 | ST10 | STC10 | BST10 | AST10 |
| 1-1/4" | 50 | ST15 | STC15 | --- | --- |
| 1-1/2" | 50 | ST20 | STC20 | --- | --- |
| 2" | 25 | ST25 | STC25 | --- | --- |

NOTE: For additional information on pipe dimensions please reference dixonvalve.com.

NPT Threaded End No Knurl



| Size | Opt Qty | Unplated Steel Part # | Plated Steel Part # | Brass Part # | Aluminum Part # |
|--------|---------|-----------------------|---------------------|--------------|-----------------|
| 1-1/4" | 50 | --- | --- | BST15 | AST15 |
| 1-1/2" | 50 | --- | --- | BST20 | AST20 |
| 2" | 25 | --- | --- | BST25 | AST25 |
| 2-1/2" | 10 | ST30 | STC30 | BST30 | AST30 |
| 3" | 10 | ST35 | STC35 | BST35 | AST35 |
| 4" | 4 | ST40 | STC40 | BST40 | AST40 |
| 5" | 4 | ST50 | STC50 | --- | AST50 |
| 6" | 2 | ST60 | STC60 | --- | AST60 |
| 8" | 2 | ST80 | STC80 | --- | --- |
| 10" | 1 | ST100 | STC100 | --- | --- |
| 12" | 1 | ST120 | STC120 | --- | --- |



| Size | Opt Qty | 316 Stainless Steel Part # | Hastelloy® Part # |
|--------|---------|----------------------------|-------------------|
| 1/2" | 50 | RST1 ¹ | --- |
| 3/4" | 50 | RST5 ¹ | --- |
| 1" | 50 | RST10 | --- |
| 1-1/4" | 50 | RST15 | --- |
| 1-1/2" | 50 | RST20 | --- |
| 2" | 25 | RST25 | HST25 |
| 2-1/2" | 10 | RST30 | --- |
| 3" | 10 | RST35 | HST35 |
| 4" | 4 | RST40 | --- |
| 5" | 4 | RST50 | --- |
| 6" | 4 | RST60 | --- |
| 8" | 2 | RST80 | --- |

¹ Made from investment casting

NOTE: For additional information on pipe dimensions please reference dixonvalve.com. King Crimp® fittings, ferrules, and sleeves can be found on pages 5 - 17.