



Materials/Finishes:	Plain Malleable Iron (218B)	Electro-Galvanized (218G)
Variants:	N/A	
Service:	Designed for the suspension of a hanger rod from the center of an I-beam. The clamp accommodates flange widths of 2-3/8" - 7". Flange thickness not to exceed .60 inches. Normally used in conjunction with figure 157 extension piece. Figure 157 provides 1" of vertical adjustment.	
Approvals:	When used with FIG. 157 Extension Piece, complies with Federal Specification WW-H-171-E (Type# 30), A-A-1192 A (Type# 30) and Manufacturers' Standardization Society MSS SP-58 and SP-69 (Type# 30).	
Ordering:	Specify figure number and finish	
Notes:	For complete assembly with extension piece see FIG. 229	

A (7/8" MAX ROD)	C ROD TAKE OUT FOR WIDTH OF BEAM FLANGE						BOLT DIA	WGT EACH (lbs)	MAX REC LOAD (lbs)
	2-3/8	3	4	5	6	7			
CLAMP ONLY	3-1/2	3-7/16	3-5/16	2-15/16	2-9/16	1-7/8	7/16	2.49	1365

PROJECT INFORMATION			APPROVAL STAMP	
Project:			Notes:	
Address:				
Contractor:				
Engineer:				
Date:				
Approved	Approved as Noted	Not Approved		