



QTY.	PIPE SIZE NPS	A (IN)	PRESSURE* (PSI)	NOTES	MAX INTERMITTENT OFFSET FROM C
	2"	12	516		1/8"
	2-1/2"	14	387		1/8"
	3"	14	316		1/8"
	4"	16	232		1/8"
	5"	17	191		1/8"
	6"	18	165		1/8"
	8"	20	234		1/8"
	10"	24	230		1/8"
	12"	25	161		1/8"

\*FOR SAFE WORKING PRESSURE ABOVE 70°F,  
MULTIPLY PRESSURE SHOWN AT 70°F TIMES  
CORRECTION FACTOR OF REQUIRED TEMP.

TEMP °F	FACTOR
70	1.0
150	.95
200	.91
250	.88
300	.85
350	.81
400	.78
450	.77
500	.77
600	.76

**NOTES:**

**NSF 372 - LEAD FREE:** The wetted surface of this product contacted by water contains less than one quarter of one percent (0.25%) of lead by weight. Material complies with state codes and standards where applicable, requiring reduced lead content.

REV.      DRAWN BY: AM      Date: 1/21/2019



5331 Quam Ave NE  
St. Michael, MN 55376  
Phone: 763-201-2151  
Fax: 763-201-2134  
Email: sales@engineeredflex.com

Customer:

Project:

Style:      STAINLESS STEEL FLEX CONNECTOR

SCALE:      DRAWING NUMBER:

NONE