




45° Lateral  
**150# Malleable Iron**  
Inches / Pounds



| Size  | A    | B    | Approximate Weight (in Pounds) |
|-------|------|------|--------------------------------|
| 3/8   | 1.93 | 1.43 | 0.27                           |
| 1/2   | 2.32 | 1.71 | 0.38                           |
| 3/4   | 2.77 | 2.05 | 0.58                           |
| 1     | 3.28 | 2.43 | 1.00                           |
| 1 1/4 | 3.94 | 2.92 | 1.54                           |
| 1 1/2 | 4.38 | 3.28 | 2.00                           |
| 2     | 5.17 | 3.93 | 3.00                           |
| 2 1/2 | 6.25 | 4.73 | 4.64                           |
| 3     | 7.26 | 5.55 | 8.00                           |
| 4     | 8.98 | 6.97 | 14.34                          |

- \*Malleable Castings conform to ASTM A197***
- \*Hot-Dipped Galvanized Fittings conform to ASTM A153***
- \*Malleable Fitting Dimensions conform to ASME B16.3***
- \*Malleable Bushings, Plugs and Locknuts conform to ASME B16.14***
- \*Malleable Unions conform to ASME B16.39***
- \*NPT Threads on all fittings conform to ASME B1.20.1***