



Materials/Finishes:	Plain Carbon Steel (909BI)	Hot-Dip Galvanized(909HDGI)
	T-316 Stainless Steel (909SX)	
Variants:	Domestic	Oversized Tap
	Special Thread Direction	
Service:	Designed for use on high temperature piping installations.	
Approvals:	Complies with Manufacturers' Standardization Society MSS SP 58 and SP 69 (Type# 14).	
Ordering:	Specify size number, rod size, finish and part number. If other than standard dimension sizes required, specify size number, rod size, pin size and grip.	
Notes:	Forged clevis are standardly supplied with pin and cotter pins. When figure number 909 I is supplied hot-dip galvanized the threading is not tapped oversize. Variant items pattern may vary. Cut sheet available upon request.	

SIZE A	CLEVIS SIZE NO.	B	C	D	G GRIP	P PIN DIA.	T	W	WGT EACH (lbs)	MAX REC LOAD (lbs)	
										650°F	750°F
3/8-16	2	3-9/16	5/8	1-7/16	5/8	9/16	5/16	1-1/16	1.0	730	540
1/2-13	2	3-9/16	5/8	1-7/16	5/8	11/16	5/16	1-1/16	1.0	1350	1010
5/8-11	2	3-9/16	5/8	1-7/16	5/8	13/16	5/16	1-1/16	1.1	2160	1610
3/4-10	2-1/2	4	1	2-1/2	3/4	15/16	5/16	1-3/16	2.3	3230	2420
7/8-9	2-1/2	4	1	2-1/2	3/4	1-1/16	5/16	1-3/16	2.5	4480	3360
1-8	3	5-1/16	1-1/4	3	1-1/4	1-3/16	1/2	1-5/8	5.1	5900	4420
1-1/8-7	3	5-1/16	1-1/4	3	1-1/4	1-5/16	1/2	1-5/8	5.2	6230	5560
1-1/4-7	3	5-1/16	1-1/4	3	1-1/4	1-7/16	1/2	1-5/8	5.6	9500	7140
1-1/2-6	3-1/2	6-3/16	1-1/2	3-5/8	1-1/2	1-11/16	9/16	2	8.1	13800	10370

PROJECT INFORMATION			APPROVAL STAMP	
Project:			Notes:	
Address:				
Contractor:				
Engineer:				
Date:				
Approved	Approved as Noted	Not Approved		