



Materials/Finishes:	Pre-Galvanized (310G)	Plastic Coated (310PC)
Variants:	Pre -Galvanized, 3/16" Felt-lined: 1/2" - 2" (310GFL)	
Service:	Designed for the suspension of insulated and non-insulated pipe lines. The plastic coated band hanger protects the pipe from the steel surface of the hanger and is designed to reduce noise, vibration and prevents electrolysis between pipe and the hanger.	
Approvals:	Complies with Manufacturers' Standardization Society MSS SP-58 and SP-69 (Type# 10). UL approved on sizes 3/4" - 8". FM approved on sizes 3/4" - 2".	
Ordering:	Specify figure number, finish and pipe size.	

PIPE SIZE	PIPE OD	A	B	C	E	F	G	WGT EACH (lbs)	MAX REC LOAD (lbs)
1/2	0.840	3/8	2-1/2	2-15/16	1-5/8	1-13/16	7/8	0.08	400
3/4	1.050	3/8	2-7/16	2-15/16	1-9/16	1-1/16	7/8	0.08	400
1	1.315	3/8	2-9/16	3-1/4	1-11/16	1	7/8	0.08	600
1-1/4	1.660	3/8	2-1/2	3-5/16	1-5/8	13/16	7/8	0.10	600
1-1/2	1.900	3/8	2-11/16	3-5/8	1-13/16	7/8	7/8	0.10	600
2	2.375	3/8	3-3/8	4-9/16	2-1/2	1-5/16	7/8	0.12	600
2-1/2	2.875	1/2	3-13/16	5-1/4	2-3/4	1-5/16	1-1/16	0.32	600
3	3.500	1/2	4-3/16	5-15/16	3-1/8	1-3/8	1-1/16	0.35	600
3-1/2	4.000	1/2	4-7/16	6-7/16	3-3/8	1-3/8	1-1/16	0.39	600
4	4.500	5/8	5	7-1/4	3-7/8	1-5/8	1-1/8	0.43	1000
5	5.563	5/8	5-5/8	8-3/8	4-1/2	1-3/4	1-1/8	0.65	1000
6	6.625	3/4	7-3/16	10-1/2	5-13/16	2-1/2	1-3/8	1.09	1250
8	8.625	3/4	8-7/16	13-1/4	7-9/16	3-1/4	1-3/8	1.24	1250

PROJECT INFORMATION	APPROVAL STAMP
Project:	Notes:
Address:	
Contractor:	
Engineer:	
Date:	
Approved Approved as Noted Not Approved	